

X-BAR Print Module **Run Faster, Longer, Stronger**

Designed for high-speed, high-volume, single-pass applications, the Kao X-BAR Print Module breathes new life into your ageing Kodak printing operation.

BENEFITS OF THE KAO X-BAR

- Cost-effective - replace up to 8 Kodak modules for the cost of a new printer
- Increased uptime
- Reduce ink usage by 50%
- 1,000 FPM
- Higher quality printing - 1200x600 dpi
- Micro Electrical Mechanical Systems technology (MEMS)
- Lower cost-per-page

SUBSTRATES

- Porous bond
- High-gloss coater stock
- Films
- Foils

COMPATIBLE KAO INKS

- Aqueous Dye
- Aqueous Pigment
- Pigment Polymer
- UV-Curable
- EB-Curable

	4" X-Bar	9" X-Bar
Print Array	2 Arrays of 3 Samba G3L printheads	1 array of 6 Samba G3L printheads
Nozzles per Array	5632	11264
Print Width	119.2 mm (4.6933 inches)	238.4 mm (9.386 inches)
Cross Process dpi	1200	1200
Process resolution	300/600/600i/1200 dpi	300/600/1200
Module dimensions and weight	Height 20", Depth 7.5", Width 7.5", 45lbs	Height 11.8, Depth 9.3", Width 16", 54lbs
Fluid Station dimensions and weight	Height 40", Depth 26", Width 24", 200lbs	Height 40", Depth 26", Width 24", 200lbs
Monochrome system	black, spot colour	black, spot colour
Speed	1000 fpm @ 1200 x 600 dpi	1000 fpm @ 1200 x 300 dpi
Controller Interface	Windows 7/10	Windows 7/10
Variable Data	Yes	Yes