

# SHRINK WRAPPING MACHINE

SWM 50 | SWM 100



Max. Converting Strokes\*  
**80**  
Cycles/Minute



## IDEAL FOR

- ▶ Companies / Traders who want to wrap variety of products

## REC. ADD-ONS

- ▶ Different Infeed Conveyors
- ▶ Insertion Unit
- ▶ Drive Roll Conveyor
- ▶ Free Roll Conveyor

## ADVANTAGES

- ▶ Continuous wrapping motion without stopping machine
- ▶ Consistent wrapping performance
- ▶ Easy to operate & low in maintenance
- ▶ Lower heat loss to surroundings
- ▶ High thickness (**50+ µm**) sealing capabilities at higher speed
- ▶ Save 1000 recipes of product in PLC for quick job change
- ▶ Less wastage
- ▶ Savings in man power cost

## Technical Specification

Model	SWM 50	SWM 100
Packing Capacity* (cycles/minute)	50	80
Packaging Product Size (mm) (L x W x H) (W + H ≤ 480)	75-1000 x 80-400 x 5-180	75-1000 x 80-400 x 5-180
Max. Film Reel Diameter (mm)	300	300
Front Sealing Blade Size (mm)	500	500
Max. Film Width (mm)	610	610
Film Type	POF & LDPE	POF & LDPE
Sealing Blade Temperature (°C)	180-210	180-210
Rec. Floor Space (L x W x H) (meter)	13 X 6 X 4	13 X 6 X 4

\* Depends upon product size, product type, Film type & thickness.

\* Rec. Floor Space is considered for offline machine.

## END PRODUCT

